

# Three Phase Hybrid Inverter

## SUN- 6 / 8 / 10 / 12 K-SG04LP3-EU/AU



100%

100% unbalanced output, each phase  
Max. output up to 50% rated power

48

48V low voltage battery, transformer isolation design

6

6 time periods for battery charging/discharging

240

Max. charging/discharging current of 240A

16

Frequency droop control, Max.16pcs parallel



DC couple and AC couple to retrofit existing solar system



Support storing energy from diesel generator

**Deye**

Clean Power For You

Model	SUN-6K-SG04LP3 -EU/AU	SUN-8K-SG04LP3 -EU/AU	SUN-10K-SG04LP3 -EU/AU	SUN-12K-SG04LP3 -EU/AU
<b>Battery Input Data</b>				
Battery Type	Lead-acid or Li-Ion			
Battery Voltage Range (V)	40~60			
Max. Charging Current (A)	150	190	210	240
Max. Discharging Current (A)	150	190	210	240
Charging Curve	3 Stages / Equalization			
External Temperature Sensor	Yes			
Charging Strategy for Li-Ion Battery	Self-adaption to BMS			
<b>PV String Input Data</b>				
Max. DC Input Power (W)	7800	10400	13000	15600
PV Input Voltage (V)	550 (150~800)			
MPPT Range (V)	200-650			
Start-up Voltage (V)	160			
PV Input Current (A)	13+13	13+13	26+13	26+13
Max. PV ISC (A)	17+17	17+17	34+17	34+17
No.of MPPT Trackers	2			
No.of Strings Per MPPT Tracker	1+1	1+1	2+1	2+1
<b>AC Output Data</b>				
Rated AC Output and UPS Power (W)	6000	8000	10000	12000
Max. AC Output Power (W)	6600	8800	11000	13200
Peak Power (off grid)	2 times of rated power, 10 S			
AC Output Rated Current (A)	9	12	15	18
Max. AC Current (A)	13.5	18	23	27
Max. Continuous AC Passthrough (A)	50			
Output Frequency and Voltage	50/60Hz; 230/400Vac (Three phase)			
Grid Type	Three Phase			
Current Harmonic Distortion	THD<3% (Linear load<1.5%)			
<b>Efficiency</b>				
Max. Efficiency	97.60%			
Euro Efficiency	97.00%			
MPPT Efficiency	99.90%			
<b>Protection</b>				
PV Input Lightning Protection	Integrated			
Anti-islanding Protection	Integrated			
PV String Input Reverse Polarity Protection	Integrated			
Insulation Resistor Detection	Integrated			
Residual Current Monitoring Unit	Integrated			
Output Over Current Protection	Integrated			
Output Shorted Protection	Integrated			
Output Over Voltage Protection	Integrated			
Surge protection	DC Type II / AC Type II			
<b>Certifications and Standards</b>				
Grid Regulation	IEC61727, IEC62116, IEC60068, IEC61683, NRS 097-2-1			
Safety EMC / Standard	IEC62109-1/-2, IEC61000-6-1, IEC61000-6-3, IEC61000-3-11, IEC61000-3-12			
<b>General Data</b>				
Operating Temperature Range (°C)	-25~60°C, >45°C Derating			
Cooling	Smart cooling			
Noise (dB)	<45 dB			
Communication with BMS	RS485; CAN			
Weight (kg)	34.5			
Size (mm)	422W×658H×281D			
Protection Degree	IP65			
Installation Style	Wall-mounted			
Warranty	5 years			